

Product G4016 | NR/SBR white 65Sh FDA

Product-Number

G4016

Product-Designation

NR/SBR white 65Sh FDA

Manufacturer

WiCo Wichmann, Otto & Cie GmbH + Co. KG

Product

Layout: without inlay Color: white

Surface: smooth on both side

Description

Medium-hard NR/SBR quality with excellent mechanical properties.



Approvals: Certified according to FDA 21 – CFR § 177.2600 (e) and BfR XXI Category 4 for

Food

Technical Specification

Material

NR/SBR

Hardness acc. to DIN ISO 7619-1

65 ± 5 °Shore A

Density acc. to DIN EN ISO 1183-1

1,43 g/cm³

Tensile Strength acc. to ISO 37

8 MPa


Elongation at Break acc. to ISO 37

380 %

Operation Temperature Range

-30/+70 °C

Stabilities



6: excellent; 5: very good; 4: good; 3: medium; 2: moderately.; 1 nonresistance.

Available Dimensions

Alaialmana in mana	1 4			4			0	40
thickness in mm	1	2	3	4	5	О	8	10
length in m	up to 10							
width in mm	up to 1400							


Notes: May 2021

Our advice is given to the best of our knowledge, but only as a non-binding reference and does not exempt our own examination of the products supplied by us for their suitability for the intended procedures and purposes. The specified technical data are guide values, i.e., experience values from longer production periods. The processing of our products is beyond our control and is therefore exclusively within your area of responsibility. Of course, we guarantee the perfect quality of our products according to our general sales and delivery conditions. Due to raw material and production, as well as by external influences (temperature, humidity, etc.), the stated values can fluctuate by up to \pm 25%.




Product Group G40 | NR/SBR

Tensile Strength



Elongation at Break



Notes: May 2021

Our advice is given to the best of our knowledge, but only as a non-binding reference and does not exempt our own examination of the products supplied by us for their suitability for the intended procedures and purposes. The specified technical data are guide values, i.e., experience values from longer production periods. The processing of our products is beyond our control and is therefore exclusively within your area of responsibility. Of course, we guarantee the perfect quality of our products according to our general sales and delivery conditions. Due to raw material and production, as well as by external influences (temperature, humidity, etc.), the stated values can fluctuate by up to \pm 25%.




Die Lösung macht den Unterschied.

Operation Temperature Range



Stabilities



Notes: May 2021

Our advice is given to the best of our knowledge, but only as a non-binding reference and does not exempt our own examination of the products supplied by us for their suitability for the intended procedures and purposes. The specified technical data are guide values, i.e., experience values from longer production periods. The processing of our products is beyond our control and is therefore exclusively within your area of responsibility. Of course, we guarantee the perfect quality of our products according to our general sales and delivery conditions. Due to raw material and production, as well as by external influences (temperature, humidity, etc.), the stated values can fluctuate by up to \pm 25%.