



Die Lösung macht den Unterschied.

Product ES4 | Adhesive Film

Product-Number

ES4

Product-Designation

Adhesive Film

Description

Adhesive film as an assembly aid for fixing and splicing. This adhesive film is highly resistant against ageing, UV and plasticizer and has a high operation temperature range.

Manufacturer

WiCo Wichmann, Otto & Cie GmbH + Co. KG

Product

Backing Material:	non
Total Thickness:	0,1 mm
Cover:	PP silicone film white
Base Composition:	acrylate dispersion

Technical Specification

Adhesive Strength

25 N / 25 mm

Shear strength dynamic

40 N/cm²

Operation Temperature Range

-40/+120°C

Stabilities

Plasticizer:	very good resistant
Ageing:	very good resistant

Notes:

May 2021

Our advice is given to the best of our knowledge, but only as a non-binding reference and does not exempt our own examination of the products supplied by us for their suitability for the intended procedures and purposes. The specified technical data are guide values, i.e., experience values from longer production periods. The processing of our products is beyond our control and is therefore exclusively within your area of responsibility. Of course, we guarantee the perfect quality of our products according to our general sales and delivery conditions. Due to raw material and production, as well as by external influences (temperature, humidity, etc.), the stated values can fluctuate by up to ± 25%.