

Die Lösung macht den Unterschied.

Product P5125 | Silicone red 60Sh

Product-Number P5125

Product-Designation Silicone red 60Sh

Manufacturer WiCo Wichmann, Otto & Cie GmbH + Co. KG

Product

Approvals:

Composition: Elastomer mixture for profiles or molded parts Color: red

Technical Specification

Material **Stabilities** VMQ Hardness acc. to DIN ISO 7619-1 Oil 6 60 ± 5 °Shore A 5 Density acc. to DIN EN ISO 1183-1 4 Ageing Fuel 3 1,2 g/cm³ Tensile Strength acc. to ISO 37 9 MPa Elongation at Break acc. to ISO 37 420 % Ozone Acid Tear Resistance acc. to DIN ISO 34-1 < 1.8 N/mm **Compression Set acc. to DIN ISO 815** Bases 34 % (22 h / 175 °C) **Operation Temperature Range** 6: excellent; 5: very good; 4: good; 3: medium; 2: moderately.; 1 nonresistance. -60/+220 °C

Certified acc. to FDA 21 - CFR § 177.2600 € for food

Description

lergenic.

Resistant to weathering and ageing, as well as ex-

cellent rubber-elastic properties and good tempera-

ture resistance. Suitable for food. Physiologically

harmless, bacteriologically indifferent, and hypoal-

Notes:

May 2021

Our advice is given to the best of our knowledge, but only as a non-binding reference and does not exempt our own examination of the products supplied by us for their suitability for the intended procedures and purposes. The specified technical data are guide values, i.e., experience values from longer production periods. The processing of our products is beyond our control and is therefore exclusively within your area of responsibility. Of course, we guarantee the perfect quality of our products according to our general sales and delivery conditions. Due to raw material and production, as well as by external influences (temperature, humidity, etc.), the stated values can fluctuate by up to $\pm 25\%$.